



XCH1020 CCTV ANALOG CAMERA TECHNICAL SPECIFICATIONS ///

Our XCH1020 CCTV weatherproof indoor/outdoor nightvision Analog CCD Camera can be placed virtually anywhere and allows you to remotely view live and recorded video from any web-based PC or mobile device. Just connect to your Controller through our Analog to Digital Converter via BNC Connection and you can be there from anywhere, anytime.

- Supports Mobile Phone Live Video

| | |
|--------------------------|--|
| Image Sensor: | 1/4" Sharp Color CCD |
| Lens: | 6mm |
| Supplied Power: | DC 12V \pm 10%,500mA |
| Resolution Support: | 420 TV Lines |
| LED Wave Length: | 30 unit 850nm Infrared LED |
| Min. Illumination: | 0 Lux nightview |
| IR Distance: | 60 feet |
| View Angle: | 45° |
| Operational Temperature: | -4° F to +104° F |
| Camera Size: | 3.5"D x 3.9"W x 6.3"H (90mm x 100mm x 160mm) |



XCH3508 CCTV ANALOG CAMERA TECHNICAL SPECIFICATIONS ///

Our XCH3508 CCTV weatherproof, indoor/outdoor, nightvision, vari-focal lens, Analog CCD Camera can be placed virtually anywhere and allows you to remotely view live and recorded video from any web-based PC or mobile device. Just connect to your Controller through our Analog to Digital Converter via BNC Connection and you can be there from anywhere, anytime.

- Supports Mobile Phone Live Video

| | |
|--------------------------|---|
| Manufacturer: | Relong |
| Image Sensor: | 1/3" SONY Super HAD CCD |
| Lens: | 3.5~8mm |
| Supplied Power: | DC 12V \pm 10%,500mA |
| Resolution Support: | 540 TV Lines |
| LED Wave Length: | 42 PCS 850nm Infrared LED |
| Min. Illumination: | 0 Lux nightview |
| IR Distance: | 90 feet |
| View Angle: | 60° |
| Operational Temperature: | 14° F to 122° F |
| Camera Size: | 6.3"D x 6.3"W x 4.7"H (160mm x 130mm x 119mm) |



HCB8830 IN/OUTDOOR VANDAL PROOF NIGHTVISION VARI-FOCAL ANALOG CAMERA TECHNICAL SPECIFICATIONS ///

Our HCB8830 weather proof/vandal proof, indoor/outdoor nightvision Vari-Focal Lens CCD Camera connects to your Controller through our Analog to Digital Converter via BNC Connection. You can connect up to 10 of these remotely accessible cameras almost anywhere in and around your home or business to view live real-time video via your web-enabled mobile phone or pc, from anywhere, anytime.

- CIF Resolution (320 x 240) at 30 Frames-per-Second
- Supports MPEG-4 and M-JPEG Dual Video Streaming
- Supports Mobile Phone Live Video

| | |
|------------------------|------------------------------|
| Image Sensor: | 1/3" Sony Super HAD CCD |
| Lens: | 3.5~8mm |
| Pixel Effective: | 768(H) x 494(V) |
| Horizontal Resolution: | 540 TV Lines |
| Distance: | 120' |
| S/N Ratio: | More Than 52 dB |
| LED Wave Length: | 48 Unit; 850 nM Infrared LED |
| Average Life: | 20,000 Hours |
| Min. Illumination: | 0 Lux Color Nightview |
| Viewing Angle: | 60° |
| Operational Temp.: | -4° to +122°F |
| Video Output: | 1Vp-p 75ΩTerminated |
| Supplied Power: | 12V DC |



HCB9020 IN/OUTDOOR VANDAL PROOF NIGHTVISION FIXED ANALOG DOME CAMERA TECHNICAL SPECIFICATIONS ///

Our HCB9020 weather proof/vandal proof, indoor/outdoor nightvision Fixed Lens CCD Camera connects to your Controller through our Analog to Digital Converter via BNC Connection. You can connect up to 10 of these remotely accessible cameras almost anywhere in and around your home or business to view live real-time video via your web-enabled mobile phone or pc, from anywhere, anytime.

- CIF Resolution (320 x 240) at 30 Frames-per-Second
- Supports MPEG-4 and M-JPEG Dual Video Streaming
- Supports Mobile Phone Live Video

| | |
|------------------------|---|
| Image Sensor: | 1/3" Sony Super HAD CCD |
| Lens: | 3.6mm |
| Pixel Effective: | 510(H) x 492(V) |
| Horizontal Resolution: | 420 TV Lines |
| Distance: | 90' |
| S/N Ratio: | More Than 52 dB |
| LED Wave Length: | 24 Unit; 840 nM Infrared LED |
| Average Life: | 20,000 Hours |
| Min. Illumination: | 0 Lux Color Nightview |
| Viewing Angle: | 52° |
| Operational Temp.: | -4° to +122°F |
| Video Output: | 1Vp-p 75Ω Y/C Separated |
| Supplied Power: | 12V DC |
| Camera Size: | 3.74"D x 3.74"W x 3.23"H (95mm x 95mm x 82mm) |